



COR SPAN

# the REFLECTION

*of craftsmanship and a*

# SMART

*investment*



## SLOPE

1:12 (Minimum Recommended Slope)

## SUBSTRATE

Open structure framing and solid substrates. It is recommended to be installed over 5/8" plywood decking with a 30 pound felt moisture barrier.

## COVERAGE

32" Coverage Panel, 7/8" Rib Height

## LENGTH

MIN. 40", MAX 40'  
(Longer lengths are available with prior coordination)

## AVAILABILITY

26 and 24 Gauge

## PERFORMANCE TEST

UL 580-94 / UL 1897-98 in accordance with Florida Building Code 2004.

## FASTENING SYSTEM

Exposed Fastener # 10 – 12 x 6 x 2" HWH

## MATERIALS

Steel Grade 80/D per ASTM A-792

## COLOR OPTIONS

Galvalume and Ceram-A-Star 1050 Stock Color - Kynar (available through special order)



**Y**ou've heard it many times before. Your home is the single largest investment most people make. And a metal roof such as Cor Span can make the most of your investment. Cor Span is extremely versatile, and the depth of the corrugations (7/8") allows for greater load requirements and increased sturdiness. With little to no upkeep as well as resistance to fire, mildew, insects and rot, a steel roof can enhance your home's market value, especially when properly installed by trained professionals who take pride in their work. ***Our dedication to quality craftsmanship is your guarantee that your smart investment will pay dividend far into the future.***

