



M PANEL



one
STRONG

look, one

SOLID

choice



SLOPE

1:12 (Minimum Recommended Slope)

SUBSTRATE

Open structure framing and solid substrates. It is recommended to be installed over 5/8" plywood decking with a 30 pound felt moisture barrier.

COVERAGE

36" Coverage Panel, 3/4" Rib Height

LENGTH

MIN. 40", MAX 40'
(Longer lengths are available with prior coordination)

AVAILABILITY

26 and 24 Gauge

PERFORMANCE TEST

UL 580-94 / UL 1897-98 in accordance with Florida Building Code 2004.

FASTENING SYSTEM

Exposed Fastener # 10 – 12 x 6 x 1 1/2" HWH

MATERIALS

Steel Grade 80/D per ASTM A-792

COLOR OPTIONS

Galvalume and Ceram-A-Star 1050 Stock Color - Kynar (available through special order)



There's a reason why metal roofing makes such a lasting impression – *because it's as durable as it is beautiful.* We're not just talking years of worry-free living. We're talking decades. The average metal roof will last longer than most people are in their homes! Strength is just one of the hallmarks of our M Panel metal roofs. With additional coverage over standard/conventional panels and pre-painted fasteners, they offer reduced labor cost and a solid, neat appearance. Maintenance is exceptionally low, and potential energy savings as well as corrosion and fire resistance adds value to your home. ***No wonder it's such a smart choice!***

